

Xerox® WorkCentre® 7830/7835/ 7845/7855 Color Multifunction Printer

WorkCentre 7800 series multifunction systems are enabled by the Xerox® ConnectKey® Controller. These simple-to-implement systems give you real, practical solutions that easily streamline how you communicate, process and share important information, simplify complex paper-driven tasks, and drive down costs while keeping your data secure.



System Specifications	WorkCentre 7830	WorkCentre 7835	WorkCentre 78/15	WorkCentre 7855
System Specifications	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Speed Color / Black-and-white	Up to 30 / 30 ppm	Up to 35 / 35 ppm	Up to 45 / 45 ppm	Up to 50 / 55 ppm
Monthly Duty Cycle ¹	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages
Recommended Average Monthly Print Volume²	8,000 to 12,000 pages	10,000 to 15,000 pages	16,000 to 20,000 pages	18,000 to 22,000 pages
Hard Drive / Processor / Memory	Minimum 160 GB / 1.2 GHz Dual-core	e / 2 GB system plus 1 GB page memory		
Connectivity	10/100/1000Base-T Ethernet, High-Sp	eed USB 2.0 Direct Print, Optional Wi-Fi (v	with Xerox® USB Wireless Adapter)	
Controller Features	Unified Address Book, Remote Control F	Panel, Online Support (accessed from the	user interface and print driver), Configurat	tion Cloning
Optional Controller	EFI Server			
Copy and Print				
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up t	o 1200 x 2400 dpi		
First-print-out Time Color / Black-and-white	As fast as 9 / 7.7 seconds		As fast as 7.5 / 6.4 seconds	As fast as 7.1 / 5.9 seconds
Page Description Languages	Adobe® PostScript® 3™, PDF, PCL® 5c /	PCL 6, XML Paper Specification (XPS®)	(Optional)	
Print Features	Print from USB, Earth Smart Driver Settings, Job Identification, Booklet Creation, Store and Recall Driver Settings, Bi-directional Status, Scaling, Job Monitoring, Color By Words			
Mobile Printing	Apple® AirPrint™, Xerox® PrintBack, Xerox® Mobile Print Solution (Optional), Xerox® Mobile Print Cloud (Optional), Mopria™ certified			
Scan				
Standard Features	Scan to Network, Scan to Email, Scan to Folder, Scan to SMB or FTP, Text Searchable PDF, PDF/A, XPS, Linearized PDF, JPEG, TIFF, Scan to USB Memory Device, Single Touch Scanning, TWAIN Support			
Optional Features	ConnectKey® for SharePoint®, ConnectKey® for DocuShare®, ConnectKey® Share to Cloud, Xerox® Scan to PC Desktop® SE and Professional, numerous solutions available through various Xerox Business Innovation Partners			
Standard Features	Internet Fax, Fax Build Job, Network S	erver Fax Enablement		
Optional Features	Fax Forward to Email or SMB, Walk-up	Fax (one-line and two-line options, incl	udes LAN Fax)	
Security				
Standard Features	McAfee® Embedded, McAfee ePolicy (ePO) Compatible, HDD Overwrite, 256-bit Encryption (FIPS 140-2 compliant), Common Criteria Certification (ISO 15408), Secure Print, Secure Fax, Secure Scan, Secure Email, Cisco® TrustSec Identity Services Engine (ISE) Integration, Network Authentication, SSL, SNMPv3, Audit Log, Access Controls, User Permissions			
Optional Features	McAfee Integrity Control, Xerox Secure Access Unified ID System®, Smart Card Enablement Kit (CAC/PIV/.NET)			
Accounting				
Standard Features	Xerox® Standard Accounting (Copy, Pr	rint, Scan, Fax, Email), Network Accounti	ng Enablement	
Optional Features	Equitrac Express®, Equitrac Office®, Equitrac Professional®, YSoft® SafeQ®, other network accounting solutions available through various Xerox Business Innovation Partners			

Device Specifications						
Control Panel Languages	3 1	International French, Italian, Germ ech, Polish, Hungarian or Romania	an, International Spanish, Dutch, Brazilian F n, Catalan	Portuguese, Swedish, Norwegian, Danish,		
Accessories	<u>'</u>					
Optional	High Capacity Feeder (HCF) Envelope Tray (Replaces Tray 1) Integrated Office Finisher (options Office Finisher LX Booklet Maker for Office Finisher LX Hole Punch for Office Finisher LX Professional Finisher Convenience Stapler (includes Wossmart Card Enablement Kit Xerox Secure Access Unified ID Sy EFI Fiery® Network Controller Walk up Fax (One- or Two-line opti Xerox® USB Wireless Adapter McAfee® Integrity Control Enabler XPS Print Option Kit	x rk Surface) sstem® ions, includes LAN Fax)				
Foreign Device Interface (FDI) (Optional)	Also known as Auxiliary Access De	vice, this is an interface to third pa	ty access control devices, such as coin mac	hines and card readers.		
Electrical Requirements						
North America	Voltage: 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 15 A					
Europe	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A	Voltage: 220-240 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 10 A				
Power Consumption	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855		
Running (Average)	110V: 641 watts 220V: 643 watts	110V: 673 watts 220V: 691 watts	110V: 750 watts 220V: 764 watts	110V: 828 watts 220V: 862 watts		
Standby Mode	110V and 220V: 62 watts		110V: 98.6 watts 220V: 95.9 watts	110V: 85.7 watts 220V: 121 watts		
Low Power Mode	110V and 220V: 59 watts					
Auto Off / Sleep mode	110V: 4.2 watts 220V: 4.8 watts (Default time to Sleep mode = 2 n	110V: 4.2 watts 110V: 4.3 watts				
Warm-up (from Off)	As fast as 194 seconds (Depender	nt on number of services registered)			
Low Power Recovery	< 9 seconds					
Operating Environment						
Required Temperature Range	50° to 82° F (10° to 28° C)					
Required Relative Humidity	15% to 85%					
Sound Power Levels	Operating 6.8 B(A), Standby: 3.6 B	B(A)				
Sound Pressure Levels	Operating: 56 dB(A), Standby: 18	dB(A)				
Dimensions and Weight	Width	Depth	Height	Weight		
Base Configuration	41.9 in. / 1,064 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	321 lbs. / 146 kg		
With Integrated Office Finisher (7830/7835 only)	44.4 in. / 1,129 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	348 lbs. / 158 kg		
With Office Finisher LX (with Booklet Maker)	65.6 in. / 1,666 mm	27.9 in. / 709 mm	45.2 in. / 1,149 mm	403 lbs. / 183 kg		
With Professional Finisher	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	526 lbs. / 239 kg		
With Professional Finisher and High Capacity Feeder	75.7 in. / 1,922 mm	27.5 in. / 699 mm	45.2 in. / 1,149 mm	590 lbs. / 268 kg		

Certifications				
	CSA Listed (UL 60950-1, Seco CB Certified (IEC 60950-1, Se GS Mark ENERGY STAR® 2.0 EPEAT GOST NOM Blue Angel Environmental Choice CE Mark Common Criteria (IEEE 2600. Citrix® Certified WHQL IPv6 Ready Cerner MEDITECH SAP	cond Edition)	ertifications.	
Paper Handling	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Duplex Automatic Document Fe	eeder			
Capacity ³	110 sheets		130 sheets (Single-pass DA	ADF)
Speed	up to 70 image per minute bl	ack-and-white and color (simplex)	up to 80 images per minute images per minute black-and	black-and-white and color (simplex) / up to 133 -white and color (duplex)
Paper Sizes Sensed	5.5 x 8.5 in. to 11 x 17 in. / A5	to A3		
Weights	16 lb. bond to 32 lb. bond / 50	gsm to 128 gsm		
Bypass Tray				
Capacity ³	100 sheets			
Sizes	Custom sizes: 3.5 x 3.9 in. to 1	2.6 x 19 in. / 89 x 98 mm to 320 x 483	mm	
Weights	16 lb. bond to 110 lb. cover /	55 to 300 gsm		
Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Heavyweight Glossy Card Stoc Hole punched Labels Letterhead Lightweight Lightweight Card Stock Reloac Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Lightweight Glossy Card Stock Region Plain Reloaded Preprinted Recycled Transparencies	ck ck Reloaded ded Reloaded		
	ets) (Optional with WorkCentre 7	830/7835 only)		
Capacity ³	Trays 1-4: 520 sheets each			
Sizes		x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 139.		
Weights	16 lb. bond to 140 lb. index /	60 to 256 gsm		

Types High Capacity Tandem Tray (Total)	Bond Card Stock Card Stock Reloaded Custom Glossy Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain Reloaded Preprinted Recycled Transparencies 3,140 sheets) (Available with all configurations)
High Capacity Tandem Tray (Total	3,140 sheets) (Available with all configurations)
Capacity ³	Tray 1: 520 sheets Tray 2: 520 sheets Tray 3: 867 sheets Tray 4: 1,133 sheets
Sizes	Tray 1: Custom Sizes from 5.5 x 7.2 in. SEF to 11.7 x 17 in. SEF / 140 x 182 mm to 297 x 432 mm Tray 2: Custom Sizes from 5.5 x 7.2 in. SEF to 12 x 18 in. SEF / 140 x 182 mm to 320 x 458 mm Trays 3-4: Standard Sizes: 8.5 x 11 in. LEF / A4, JIS B5, Executive (7.25 x 10.5 in.)
Weights	16 lb. bond to 140 lb. index / 60 to 256 gsm
Types	Bond Card Stock Custom Glossy Card Stock Hole punched Labels Letterhead Lightweight Card Stock Plain Preprinted
High Capacity Feeder (HCF) (Optio	
Capacity ³	2000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. / A4 LEF
Weights	16 lb. bond to 140 lb. index / 55 to 256 qsm
Envelope Tray (Optional - Replaces	5
Capacity ³	Up to 60 envelopes
Sizes	#10 Commercial (9.25 x 4.125 in.), Monarch, DL, C5, 6 x 9 in. Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm)
Weights	20 lb. bond to 24 lb. bond / 75 to 90 gsm
Total Capacity	
Device Total Capacity ³	5,140 sheets
Finishing	
Output Trays (Standard)	
Stacking Trays ³	Dual Offset Catch Tray — up to 250 sheets each Left-side Face up Tray — up to 100 sheets
Integrated Office Finisher (Option	al with 7830/7835)
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 256 gsm

Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)				
Office Finisher LX (Optional)					
Capacity ³	Stacking Tray: 2,000 sheets unstapled	or 1,000 sheets single stapled or 750 sh	neets dual stapled (8.5 x 11 in. / A4)		
Sizes	7.2 x 8.3 in. to 11.7 x 17 in. / 182 x 21	0 mm to 297 x 432 mm	•		
Weights	16 lb bond to 80 lb cover / 60 to 256	gsm			
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm	-			
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch	2-3 Hole Punch			
Booklet Maker for Office Finisher L	X (Score/Crease, Saddle-stitch Staple) (Optional)			
Capacity ³	40 booklets (2-15 sheets per booklet -	· 20 lb. / 80 gsm or less)			
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF				
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 g	ısm			
Score / Crease	1-15 sheets / unstapled				
Professional Finisher (Optional)					
Capacity ³	Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 or 100 stapled sets of 11 x 17 in. / A3 / SRA3				
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3	5			
Weights	16 lb. bond to 80 lb. cover / 60 to 220	gsm			
Stapling	· -	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported			
Hole Punch (Standard) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)				
Booklet Maker	Saddle-stitch 2 to 15 sheets (14 sheet: Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, SRA3 sup	s of 90 gsm or less plus 1 sheet of 169 opported	gsm)		
Convenience Stapler (Optional - In	cludes Work Surface)				
Capacity ³	50-sheet stapling 5,000 staples Requires a separate outlet				
Сору	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855	
First-copy-out Time (Letter/A4-size, from Platen to Center Tray) (Color / Black-and-white)	As fast as 8.4 seconds / As fast as 6.7 seconds	As fast as 8.2 seconds / As fast as 6.8 seconds	As fast as 7.5 seconds / As fast as 6.2 seconds	As fast as 7.1 seconds / As fast as 5.5 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1				
Quantity	1 to 9,999				
Resolution (max.)	Up to 600 x 600 dpi				
	Variable zoom from 25% to 400% in 1% increments				
Reduction / Enlargement	Variable 20011 110111 23 70 to 400 70 111	170 merennenes			

Copy Features	Authentication for Services (i.e. Auto Paper Select Auto Reduction & Enlargement Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job: (Enables page-level procollation	orogramming and also lets you proof eack, back only, printed inside and out: d graphic descriptions) option) or image)	each section or delete last section as the	job is built)
Xerox [®] Copier Assistant [®]	attached via the USB port, this	software supports text-to-speech, scre		conjunction with a customer-supplied PC access to basic and advanced copy features. x.com
Print	WorkCentre 7830	WorkCentre 7835	WorkCentre 7845	WorkCentre 7855
Print Resolution	Up to 1200 x 2400 dpi			
Print Features	Job Identification (Print ID or Be Layout / Watermark (N-up (up t Overlays Paper Selection by Attribute LAN Fax (requires optional Fax t Sample Set Saved Job (color jobs can be pri Secure Print with Timed Deletio Special Pages (exception page p Store and Recall Driver Settings	esolution (Standard, Enhanced, High) ianner, Print ID in margins on first pag to 16 pages per sheet), Multi-up, Book Kit) inted as monochrome) on programming: covers, inserts, exception	vlet layout / finishing, Fit to new paper siz	
Print from USB	Allows walk-up printing from Typ Supports direct printing from co Supported file formats: PDF, JPE Color jobs can be printed as mo	omputer via Type B USB port EG, TIFF, PS, XPS, PCL		

Operating Systems	Microsoft® Windows® XP (32- and 64-bit)		
	Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit)		
	Windows Server 2008 (32- and 64-bit) Windows Server 2012		
	Windows Vista (32- and 64-bit)		
	Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit)		
	Windows 8.1 (32- and 64-bit)		
	Mac OS 10.5, 10.6, 10.7, 10.8		
	PowerPC AIX 5 Solaris® 9, 10		
	Solaris SPARC 10		
	HP-UX® 11v2 IBM® AIX® 5		
	Redhat® Fedora® Core 15-17, 19 x86		
	Redhat Enterprise 4 and 5 openSUSE® 11 and 12		
	Ubuntu® 12, 10 x64		
	Itanium HP-UX 11i v3 Unix®		
Natural Dratacale		April 0100 ID A ID C WCD	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing NetWare: Bindery and NDS IPX/SPX, NDPS®/NEPS (with Server Gateway)	7POIL 9 100, 1PV4/1PV6, WSD	
	AppleTalk®: EtherTalk®		
	Microsoft Windows Networking over IP Bonjour®		
	IPv6		
	Secure FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, BOOTP, SNMP, WINS, SLP® v2, HTTP, HTTPS, DHCP Autonet, SSL, NTP,	DNS, SSDP	
Fonts	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox Secure Access Unified ID System®, Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
Print Solutions			
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile w burdening staff, budget or infrastructure. Getting started takes only a few mir printer. Accurate printing with true Microsoft® Office® rendering and more. Pr	nutes via the cloud. Print from any mobile device to nearly any brand of	
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or MFP without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.		
Unified Address Book for Fax, Inter	net Fax, Email and Scan to		
Features	Services supported: Fax, Internet Fax, Email, Scan to		
	Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of fax numbers, emails, etc.		
Scan	WorkCentre 7830 WorkCentre 7835	WorkCentre 7845 WorkCentre 7855	
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to no concurrent jobs)	etwork or fax jobs (priority is for return of scanned originals and printing	
Input Speed	Scan at up to 70 ipm color scanning, up to 70 ipm black-and-white – 8.5 x 11 in. / A4 LEF	Scan at up to 133 ipm color scanning, up to 133 ipm black-and-white – 8.5 x 11 in. / A4 LEF	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white), 8-bit (grayscale), 24-bit (color)		
Maximum Scan Area	11 x 17 in. / A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other MFPs Confirmation sheet options		
	Confirmation sheet options		

E	C. L. THE /THE CO. TTUD WILLIAM CO.
File Formats	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression - single or multiple pages) Searchable PDF and PDF/A (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-white and within MRC)) JPEG XPS Encrypted / Password Protected PDF (Network Scan Templates only)
	Linearized PDF
Document Management Fields (Meta Data)	Features only available in Network Scan to File Templates: • 1 to 6 user programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customized fields viewed on user interface for variable data input
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)
Supported Scan Destinations (Standard)	Local Scan to USB Drive Scan to Mailbox Remote Scan to Email Scan to PC / Server Client (SMB or FTP) Scan to Secure FTP and HTTPS Scan to Home Scan to Application
Supported Scan Destinations (Optional)	Xerox® Scan to PC Desktop® (Professional and SE) ScanFlowStore® Xerox® ConnectKey® for SharePoint® Xerox® ConnectKey® for DocuShare® Xerox® ConnectKey® Share to Cloud Various Xerox Business Innovation Partner Solutions
Authentication	Supports Kerberos (UNIX / Windows Server) SMB (Windows Server) NDS LDAP Xerox Secure Access Unified ID System® Locally on device (internal database) Convenience Authentication via Magstripe, Proximity and Smart Card (CAC / PIV and .NET) readers (optional)
Scan to Email (Standard)	
Scan Features	Email signatures (6 lines each of 128 character max), email message body (user configurable), email CentreWare IS confirmation sheet options Scan to Email S/MIME Encryption Email Signing (requires Smart Card option) Auto send to self
Directory Access	Address list via LDAP (Windows Archive Directory, Exchange, Notes, Domino) Downloaded address list (comma-separated file format) Utilizes the Unified Address Book
Scan to (Standard)	
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries)
Network Scanning – Software Solo	utions
Xerox® Scan to PC Desktop® Professional (Optional)	A desktop offering that provides advanced document imaging, archiving, editing and organization tools: • PaperPort Professional image viewing and file management software — Complete PDF functionality — Secure PDF workflow of all scanning applications • OmniPage Pro Office (for desktop/client installation) — Professional OCR software for digital archiving and document conversion • Image Retriever — provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Also includes email inbox polling capability
Xerox® ConnectKey® for ShαrePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.

Xerox® ConnectKey® Share to Cloud (Optional)	ConnectKey Share to Cloud provides organizations with powerful, easy and secure document scanning capabilities that connect your Xerox® MFP to popular cloud services and email, such as Google Docs™, SalesForce.com, Office 365 and Dropbox™ and gives employees anytime, anywhere access to their most important documents using mobile devices.
Xerox [®] ConnectKey [®] for DocuShare [®] (optional)	Xerox® ConnectKey for DocuShare, a one-step scan-to-workflow solution, simplifies the process of incorporating hard copy content into enterprise document flows. Users can easily scan documents directly into a DocuShare collection or Windows folder via a multifunction printer (MFP).
Security	
Features	Expanded Authentication Network authentication to access device and/or device services via- Kerberos (UNIX / Windows Server 2003 / Windows Server 2008), SMB (Windows Server 2003 / Windows Server 2008), NDS, LDAP Xerox Secure Access Unified ID System® Local Authentication (internal database) Smart Card authentication -144k CAC / PIV Card Support (2048 bit certificate key) /.NET Secure Data
	 Digitally signed PDF (when using Smart Card authentication) Encrypted Scan to Email Encrypted Password Protected PDF (when using Network Scan Templates only) Secure Print (up to 10 digit PIN or Network Authentication) Immediate Image Overwrite On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk FIPS 140-2 256 bit Hard Disk Encryption Expanded Authorization SA access based on network credentials Authorization per user per service User Permissions required to access Print and Print Features (e.g. color access, or time restrictions) reflects in the print driver Secure Network Access IP Filter, IPsec, IPv6, SSL v3.0, SNMPv3, HTTPs, 802.1X, Cisco® TrustSec Identity Services Engine (ISE) integration, Device Security McAfee® Embedded Security, Port disablement including USB ports, Audit Log, Hide Print Job Names, , McAfee Integrity Control (optional) Common Criteria Certification ISO 15408
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee/student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to www.office.xerox.com/software-solutions
Fax	
Network Server Fax Features	
Compatibility	ITU (CCITT) group 3 Various Xerox Business Innovation Partner Solutions
Maximum Scan Area	11 x 17 in. / A3
Fax Send Features	One- or Two-sided Scanning (up to 11 x 17 in. / A3) Add to Send List (50 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi
Internet Fax Features	
Capability	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients
Directory Access	Utilizes the Unified Address Book
Send / Receive	Multi-page TIFF, Image only PDF
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)
Network Protocols	SMTP (send), POP3 (receive)
Compliance	ITU-T T.37 compliant
Walk-up Fax Features (Optional (Customer-installable) – 1 and 2 lines)
Compatibility	ITU (CCITT) Group 3
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time ATA analog terminal adapter utilizing T38 (optional)
Compression / Speed	MH/G3, MMR/SG3
Resolution	Walkup Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes

Fax Send Features	LAN Fax (fax from print driver)
	Auto Fax Transmission Reduction Page-by-page Job Status at the Machine
	Delay Start, Build Job, Favorites Automatic Memory Resend
	Automatic Cover Sheets
	PSTN Fax Batch Send (up to memory capacity)
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password Protected Mailboxes
	Secure Receive Receive Timestamp Auto Answer Delay
Fax Forward	Forward to Email or SMB Location Fax Forward on Receive Only
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report
Directory Access	Utilizes the Unified Address Book Group fax available
Auto Redial	Up to 14 attempts (per country requirements) • 1 to 25 minute intervals
Auto Resend	Up to 5 attempts
Device Management	
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213), Host Resources MIB RFC 2790, Printer MIB RFC 1759 v.2
Xerox® CentreWare® Web	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: Works with any SNMP-managed printer from any manufacturer. Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. Requires Windows XP, Vista or Windows 7 and Internet Explorer 6.0 and higher. CentreWare Integration available for Tivoli® NetView®, Unicenter TNG®, Microsoft Management Console (MMC), HP® OpenView®
Novell NDPS/NEPS	Server gateway application: centralized management tool.
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® printers and MFPs. And as an SAP customer you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and MFPs are available to download. www.office.xerox.com/software-solutions
Xerox [®] Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAPenvironment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at www.office.xerox.com/software-solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction systems by storing Xerox® software, as well as, the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at www.office.xerox.com/software-solutions
CentreWare Internet Services – Int	egrated Web Pages Provided by the Device
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS, TXT, RRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device

_	
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x
	Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x
	Operα 11.x
<u> </u>	Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish or Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Accounting	
Xerox® Standard Accounting (Standard)
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User accounts (User ID)
-	Up to 500 General accounts (Client)
	Up to 498 Group accounts (Department)
Feαtures	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry standard CSV file
Accounting Options – Network	k Accounting – Third Party Enablement
	Enhanced network accounting with up to the minute data on how the system is being used
	 Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com
	• Security enhancements with the addition of HTTPS protocol support
	Device requests account authentication from third party server enabling larger databases of users and accounts
	 Accept Authentication Login at control panel and pass to third party Networking Account Interface with third party accounting terminal for accounting user interface
EFI Fiery Network Controller (
Processor	2.9 GHz, Intel® Pentium® G850 Dual-Core
Memory (ESS)	1 GB
System Disk	500 GB HDD
Print Languages (PDL)	PostScript v 3019
Features	Command WorkStation capability via a PC or MAC (customer to provide) with Queue Management
	Job Preview Job Merge
	Change Job Properties
	PANTONE® Color Tables
	Expert Color Settings: Profile, Rendering and Simulation
	FreeForm – Variable Data capabilities Booklet Maker 4.0 – booklet wizard to create booklets
	Print from USB flash drive
	Paper Catalog
	Secure Erase EFI PrintMe
	Fiery® VUE
Connectivity	10Base-T/100Base-TX/1000Base-T Ethernet
Optional	Mini-bundle (Spot On, Auto Trapping, Hot folders, Virtual Print)
	Network Switch to connect both printer and Fiery Controller to Network

Supplies			
Toner Cartridges (Metered) ³	Black	26,000 pages	006R01509
	Cyan	15,000 pages	006R01512
	Magenta	15,000 pages	006R01511
	Yellow	15,000 pages	006R01510
Toner Cartridges (Sold) ³	Black	26,000 pages	006R01513
	Cyan	15,000 pages	006R01516
	Magenta	15,000 pages	006R01515
	Yellow	15,000 pages	006R01514
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064
Staple Cartridges	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	for Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897
	for Professional Finisher Booklet Maker (4 cartridges per carton)	5,000 each cartridge	008R12925
Staple Refills	for Integrated Office Finisher, Office Finisher LX, Professional Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
Xerox® Smart Kit®			
Drum Cartridge ⁴	1 Cartridge per Color	125,000	013R00662
Waste Toner Container ⁴	1 Cartridge	43,000	008R13061

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, call **1-800-ASK-XEROX** or visit us at www.xerox.com/office



² Expected regular monthly throughput

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.